

- 600 Denier Polyester
 With Urethane Coating
- Water Repellent
- Mildew Resistant
- Protects Also Against: Weed Wackers, Rodents, And UV Rays

Super Fast HVAC Foam Protection

diameters quickly and easily for a tight fit.

With the introduction of new building code regulations regarding protection of foam insulation on HVAC line sets, Techflex has developed a new lightweight wrap to assist installers with code compliance.

Our new Dura HVAC Wrap is constructed of a tightly woven breathable polyester shell that offers protection from wind, rain, mildew, UV rays and abrasion. The extra wide hook and loop closure assists in covering multiple



Protect your HVAC foam insulation from harmful UV rays with Dura HVAC Wrap.





BUILDING CODE COMPLIANT C403.2.10.1 & R403.4.1

Piping insulation exposed to the weather shall be protected from damage, including that due to sunlight, moisture, equipment maintenance and wind, and shall provide shielding from solar radiation that can cause degradation of the material. Adhesive tape shall not be permitted.



Nominal Size	Part #	Wall Thickness	Hook & Loop	Standard Spool Put-Ups		Available	Lbs/
				Bulk Spool	Shop Spool	Colors	100′
1 1/2"	FPW1.50BK	.013"	1 1/2"	150′	25′	Black (BK)	4.71
2"	FPW2.00BK	.013"	1 1/2"	150′	25′	Black (BK)	5.34
2 1/2"	FPW2.50BK	.013"	1 1/2"	150′	25′	Black (BK)	5.89
3″	FPW3.00BK	.013"	1 1/2"	150′	25′	Black (BK)	6.66
3 1/2"	FPW3.50BK	.013"	1 1/2"	150′	25′	Black (BK)	7.10
4"	FPW4.00BK	.013"	1 1/2"	150′	25′	Black (BK)	7.84
4 1/2"	FPW4.50BK	.013"	1 1/2"	150′	25′	Black (BK)	8.36