



- **Highly Reflective**
- **Easy to Install**
- **Cut And Abrasion Resistant**
- **Resists Gasoline and Engine Chemicals**



No special tools or skills required for installation.

Reflective, Split Semi Rigid Sleeving For Easy Installation

Ease of installation makes F6® REFLEX® (F6R) the most suitable reflective sleeving for applications where disassembly of the components is not a viable option. Just open the lateral split and slip the sleeving over wires or cables. The sleeving will snap back in place and provide an extra measure of safety under low light conditions.



F6® Reflex® is available in clear. Patent pending.

Under low light conditions, the retroreflective strands in F6® Reflex® sleeving reflect light up to 1,500 times more efficiently than bright white sleeving.




See pg. 123 for bike kits.

Nominal Size	Part #	Wall Thickness	Standard Spool Put-Ups		Available Colors	Lbs/100'
			Bulk Spool	Shop Spool		
3/16"	F6R0.19CL	0.025"	200'	100'	Clear (CL)	0.58



- **Highly Reflective**
- **Easy to Install**
- **Expands up to 150%**
- **Halogen Free**
- **Resists Gasoline and Engine Chemicals**

Under low light conditions, the retroreflective strands in FLEXO® Reflex® sleeving reflect light up to 1,500 times more efficiently than bright white sleeving.



Reflects Light 360° Up To 675'

FLEXO® REFLEX® (RFN) is our polyethylene terephthalate material braided together with highly reflective 3M Scotchlite retroreflective monofilament. This unique combination provides a high level of wire and cable protection with the added advantage of extraordinary 360 degree, on-axis reflectivity. RFN is up to 1,500 times brighter than plain white under identical conditions and will provide high visibility safety on wires, hoses, cables, bicycle and motorcycle cables, stage wiring, and virtually anything else up to 675' away. Reflective even under low light conditions. Patent pending.

Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available Colors	Lbs/100'
		Min.	Max.	Bulk Spool	Shop Spool		
1/8"	RFN0.13CL	1/16"	1/4"	1,000'	100'	Clear (CL)	0.29
1/4"	RFN0.25	3/16"	3/8"	1,000'	100'	CL & BK	0.33
1/2"	RFN0.50	1/4"	1"	500'	100'	CL & BK	0.52
3/4"	RFN0.75	3/8"	1 3/8"	250'	75'	CL & BK	0.63



1 (833) SLEEVING
www.techflex.com